



R717 refrigerant grade ammonia. High quality and natural.



Introduction R717 is refrigerant grade high purity ammonia (NH₃). The product typically is 99.98% pure with minimal levels of moisture (< 200 ppm) and other impurities (< 3 ppm oil), making it ideal for use in all types of refrigeration systems, especially in the air conditioning industry. All cylinders and drums are equipped with dip tube.

Specifics/facts Ammonia 3.8 (99,98%). Max 200 ppm H₂O and oil max 3 ppm

Product specification	Cylinder size in litres	Content in kg	Valve	Country	Item number
	26	13,8	double	SE/NO/DK	107094
	61	32	double	SE/NO/DK/FI/EE/LT/LV	113139
	108	57	single	SE/NO/DK/FI/EE/LT/LV	107095
	108	57	single	SE/NO/DK/FI/EE/LT/LV	107096*
	127	Waste		SE/NO/DK	116997**
	900	475	2 valves	SE/NO/DK/FI/EE/LT/LV	113233
	995	527	2 valves	SE/NO/DK/FI/EE/LT/LV	107587

*without diptube. **waste-cylinder. 61L upon request in SE/NO

- Advantages of R717**
- Zero ozone depletion potential and zero global warming potential
 - Excellent thermodynamic properties leading to a high energy efficiency
 - Wide range of operating temperatures (-50 to +15°C)

www.linde-gas.se, www.linde-gas.no, www.linde-gas.fi, www.linde-gas.dk, www.linde-gas.ee,
www.linde-gas.lv, www.linde-gas.lt, www.linde-gas.is